

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**  
**(Attorney Reference No. 350/001/CIP)**

**TITLE:** Automated Microtome Blade Changer

**INVENTORS:** Kendall B. Hendrick  
Miroslav Holubec  
Darin McDaniel  
William Richards  
Vincent Rizzo

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

## Related Applications

This application is a continuation-in-part of commonly assigned U.S. Serial Number 09/562,270, filed April 29, 2000.

## Background

### 1. Field of the Invention

The present invention is directed to apparatus for use in preparing tissue sections for use in diagnostic histopathology and, more particularly, to an apparatus that automatically changes the blades of a microtome without exposure of the user to the cutting edges of the blades.

### 2. Description of Related Art

Microtomes have been used for many years to meet the exacting requirements necessary for thin sectioning of paraffin-embedded tissue. Essentially, microtomes are holders for razor-sharp metal blades, against which a block of paraffin-embedded tissue is moved in an up-and-down motion. Concurrently, either the tissue block is advanced against the blade, or vice versa, so that with each up or down stroke, a thin slice or "section" of tissue is cut from the block. The blades are highly engineered for the precise requirements of tissue sectioning. Specifically, the blades are capable of cutting sections as thin as 1 $\mu$ m.

The present practice for tissue sectioning requires the blades be changed as they become dulled. This necessitates alleviating the pressure that the blade holder puts on the blade to keep it in place, usually by removing a clamping mechanism. Once the clamp is removed, the blade can be lifted off of the rest. Usually, this is accomplished by grasping the blade at an edge and discarding it in a sharps container, all of which is done by hand. This exposed the user to the edges of the blade, and of course the potential of serious injury. Additional exposure to the sharp blade occurs when loading a new blade and re-clamping it in position.

U.S. Patent No. 3,667,330 (Kobernick) discloses an automated microtome assembly which includes a continuous flexible steel blade whose ends are mounted upon feed and takeup reels for intermittent motor-driven advancement to enable advancement

of new cutting surface without contact by a user. The changing of the knife edge may be actuated manually or automatically. The '330 patent does not disclose a method or apparatus for the changing of individual blades, or provide safety features for the changing of the blade.

5 U.S. Patent 4,207,790 (Endo) is directed to a knife holder and blade cassette for microtomes. The knife holder comprises a base plate and a holder plate for holding the knife edge onto the base plate. The blade cartridge is spring-loaded for biasing the blades upwardly towards the exit from the cartridge. To replace a blade, the user must first  
10 loosen the bolts holding the knife holder plate down, then engage the cartridge with the edge of the knife holder assembly, and finally slide a new blade out of the cartridge and into contact with the dull blade, thereby positioning a new blade beneath the holder plate and simultaneously pushing the dull blade out of position. There is no disclosure related to automation of the process, what happens to the spent blade, or safety features.

Blade changers for hand-held shavers are known. U.S. Patent 1,817,512  
15 (Gaisman) and 2,741,837 (Breazeale) disclose a cartridge containing individual blades wherein the blade is manually dispensed from the cartridge using an ejector, and at the end of the ejector stroke the blade is located in the cutting position, and the used blade is received in a take-up cartridge (see Gaisman, Fig. 11). U.S. Patent 2,653,379 (Austin) discloses a box with a cartridge on either side of a razor. A slider pushes a new blade  
20 from the first cartridge onto the razor, which pushes the used blade into the second cartridge. U.S. Patent 2,679,685 (Austin) discloses a razor blade changer where advancing a pusher causes a blade in supply cartridge C to advance into the razor and push the used blade out into take-up cartridge D. When cartridge C is empty, it is put in place of discarded cartridge D to act as the new take-up cartridge, and a full supply  
25 cartridge is put in place of cartridge C.

Patents on razor blade containers include US Patent 2,592,138 (Gwoosh et al.) for a razor blade package which teaches the use of a coil spring to bias blades towards the dispenser opening of a blade container. The top has a thumb opening to allow manual advance of the blades. US Patent 2,604,979 (Roberts) shows a spring-loaded blade  
30 container which uses a leaf-spring. US Patent 2,775,366 (Willhelm) discloses the use of a compression spring to urge a plurality of blades towards the package opening. US

Patent 5,409,133 (Gringer) is a spring-loaded blade dispenser wherein the entire top except guide rails, is open for application of a manual dispensing force. The dispenser is also capable of receiving spent blades back through a disposal opening 34 (see Figs. 9-10). None of the above mentioned patents are adapted for automatic use.

5 There is a need for an automated microtome blade changing system that safeguards the user against being seriously injured, and enhances the work flow in the pathology laboratory.

### Summary of the Invention

10 The invention is directed to an automated rotary microtome blade changing apparatus, comprising an upper stage adapted to releasably engage a supply and a waste cartridge, the upper stage having a loading segment adapted to engage and move blades contained within said supply cartridge into a cutting position; clamping means for releasably holding the blades in place for cutting operations; power means for driving the  
15 movement of blades and clamping mechanisms; and electronic control means for integrating all of the functions of the apparatus.

The invention is also directed to an automated rotary microtome blade changing apparatus, comprising an upper stage adapted to releasably engage a supply and a waste cartridge, the upper stage having a reverser shuttle adapted to engage and move blades  
20 contained within said supply cartridge into a cutting position; clamping means for releasably holding the blades in place for cutting operations; power means for driving the movement of blades and clamping mechanisms; and electronic control means for integrating all of the functions of the apparatus.

Also described herein is an improved blade supply cartridge wherein the cartridge  
25 comprises a body, a spring, a dispensing tab, and blades, wherein the improvement comprises a toothed portion on said dispensing tab adapted to engage mating gear teeth on said blade changer.

Also described herein is an improved blade supply cartridge wherein the cartridge comprises a body, a spring, a dispensing tab, and blades, wherein the improvement  
30 comprises a touch memory device in contact with the cartridge, the touch memory device programmed to contain content information relating to said cartridge.

It is an object of the present invention to provide a fully automated blade changer for the histopathology laboratory that reduces and hopefully eliminates the chances of being cut accidentally during routine laboratory operations with the microtome blades.

It is another object of the present invention to provide a new blade cartridge that, in cooperation with a microcontroller in the blade changer, can track blade useage and signal the user when blades are running low.

These and other advantages of the present invention will become clear in the following description of the invention.

### **Brief Description of the Drawings**

Figure 1 is a front elevational view of the automated blade changer with both the upper and lower stages shown.

Figure 2 is a front elevational view with partial cutaway of the upper stage of the device.

Figures 3A-3D show, respectively, a perspective view of a blade supply cartridge, a top view of the same, a sectional view along lines C-C shown in 3B, and a blade adapted for use with the invention.

Figures 4A-D are front elevational views of the sequence of positions that a blade typically arrives at during loading.

Figures 5A-C are, respectively, a front elevational perspective view of a dedicated waste cartridge, a top view of the same, and a sectional view along lines D-D.

Figure 6 is a block diagram of the electronics controlling the blade changer.

Figure 7 is a front elevational view of the second embodiment of the automated blade changer with both upper and lower stages shown. A cutout shows the drive shaft gearing arrangement.

Figure 8 is a front elevational view of the second embodiment of the automated blade changer with partial cutaway of the upper stage of the device.

### **Description of the Preferred Embodiments**

The purpose of this invention is to improve the safety and productivity of the process of cutting tissue blocks with a rotary microtome. It is achieved by automating the

process of loading new knife blades into the microtome and disposing of used ones. At present, cutting tissue on a microtome involves considerable handling of disposable knife blades with the technologist's bare hand. So, because the edge of the blade is razor sharp, cutting injuries are common. This risk of injury is significant even if the technologist  
 5 only comes into contact with a blade twice – once to load, once to discard – but current practice in histotechnology often greatly increases this exposure.

There are two other problems the invention ameliorates. First, with constant handling of the blade also comes a risk of infection from the tissue. With properly processed tissue there is no risk of infection, but it is possible with non-processed or  
 10 under-processed tissue that direct contact with the tissue can lead to infection. Therefore, by eliminating all physical contact with the blade, the risk of infection is significantly reduced. Secondly, the process of loading and unloading the blades by hand is somewhat time-consuming. The invention addresses this issue as well, by replacing the manual movement of blades with an automated movement of blades.

15 Thus, this invention offers to the histology laboratory increased safety, flexibility and efficiency. These features all translate to the laboratory's financial bottom line: safety translates to fewer missed work days and enhanced risk management, while flexibility and efficiency allow the laboratory to provide a maximum output of staining results with a minimum number of laboratory technicians.

20 The invention is best illustrated by reference to the following Figures 1-2. The preferred embodiments are based on a standard knife stage design. That is, the invention is contained within the upper stage body of a standard rotary microtome knife holder. In Figures 1 and 2, the upper stage body 5 is the platform for the functional portions of the blade changer apparatus. It contains the major sub-components of the blade changer,  
 25 including waste and supply blade cartridges 10, 15, respectively, clamping means, blade 100, power means and electronic control means. A general overview of the device follows, with more particularity in subsequent sections.

#### I. General overview

30 A first embodiment of the blade changer comprises lower and upper stage bodies 1, 5, respectively. With reference to Fig. 1 the microtome blade cartridges are removably

located within the upper stage body 5. The lower stage body is adaptable to a wide variety of rotary microtomes, and serves as the common interface mounting for the upper stage. The disposable blade cartridges 10, 15 are adapted to lock into the upper stage body 5 so as to provide an element of safety. The cartridges are described more fully below and in Figs. 3-5. They are releasable only when the individual blades are fully secured within the body of the cartridge. This "interlock" function can be attained in many ways, however a preferred embodiment includes an on-board microcontroller which monitors the state of operation of the blade changer. When the controller's logic functions determine that no blade edges are exposed, then the clamping plate and/or the cartridges may be released. The interlock function is more fully described below. The clamping means includes clamping plate 20, support plate 25, and clamp pivot rod 112 which together function to clamp the blade in the cutting position during use of the blade in the microtome. Loading segment 30 has a toothed gear portion rotatably mounted to engage the reciprocal teeth on dispensing tab 90. Dispensing tab 90 is integral with the supply cartridge. At a second end of the supply cartridge loading segment 30 engages loading cam 40 (Fig. 2). The function of loading segment 30 is to move dispensing tab 90 of the blade supply cartridge 15 thereby urging new blades 95 to the central cutting area. This is performed through downwardly protruding member 92 which engages a slot or hole 96 formed in the body of blade 95 (See Fig. 3) which enables dispensing tab 90 to engage the topmost blade in its stored position at the top of the stack of blades contained within supply cartridge 15. Loading cam 40 engages with the lower extending portion 32 of loading segment 30 through the groove in the surface of loading cam 40 thereby enabling rotation of loading segment 30 around shoulder screw 35. Shoulder screw 35 is anchored into upper stage body 5 and its function is to provide a pivot for loading segment 30.

Power means comprises bidirectional DC motor 50 which drives the motor gear 55, which in turn drives the drive shaft pulley 60. The purpose of the motor, gear and pulley is to rotate drive shaft 65 and thus provide the power for moving loading segment 30 from left to right, and/or from right to left; and simultaneously moving clamping plate 20 forward and backward in order to either clamp or release a blade in the cutting area. The motor is bidirectional so that clamp pivot rod 112 may be released only when the

motor is reversed. This function would require a clutch mechanism that in forward (normal) operation engages a groove in the rod, which stops the rod from being removed from the blade changer. Since removal of the rod is a precursor to removal of the clamping plate for cleaning access, this is another safety interlock feature of the device.

5       The loading cam 40 and clamping cam 45 are coordinated so that loading segment 30 can only push a new blade 95 into position when clamping plate 20 is open (pressure relieved from the blade). It is well within the skill in the art to design and position the two cams to effectuate this coordinated function. Electronic control means includes a printed circuit board 70 which contains the microcontroller and associated circuits and  
10       controls the operation of the blade changer, push-button switches 76, 77 on keypad 75, a power source 85, and safety interlocks 155. The "blade advance" signal comes to the electronic circuit from keypad 75 via blade advance switch 76. In a preferred embodiment the power for the blade changer is supplied from the on-board battery 86. Alternatively, power could be supplied from an AC source (not shown).

15       A second embodiment of the automated blade changer is depicted in Figures 7 and 8. The primary difference in this second embodiment is that loading segment 30 and the attendant gearing for it have been replaced with a reverser screw 240 and reverser shuttle 230 combination. The dispensing tab on the supply cartridge has also been modified to adapt to the shuttle. The advantages include less coordination of the motion  
20       because the shuttle reverses direction automatically as the drive shaft continues in a unidirectional fashion.

## II. Detailed Description of the Invention

25       The clamping means includes clamping plate 20, support plate 25, and clamp pivot rod 112 which together function to clamp the blade in the cutting position during use of the blade in the microtome. Support plate 25 has a thin rectangular block 27 attached on its surface which provides a ledge upon which blades in the cutting area sit. In a preferred embodiment, the ledge can be magnetized which aids in retention of the blade on the support plate. Alternatively, a ledge could be machined into its surface to  
30       provide the same support function. Clamping cam 45 engages clamping plate 20 on leaf spring 22 so that when the cam is turned, clamping plate 20 releasably engages support



plate 25, thus holding or releasing blade 100. A clamp pivot rod 112 provides a pivot point about which the clamp pivots. The rod may pass through a hole or tunnel in the plate or it may be mounted directly behind the plate. In a preferred embodiment, the rod passes through the block 21 securely attached to the plate. The rod is anchored to the upper stage body 5 at both ends through holes adapted for receiving the rod (not shown). Other clamping means come within the spirit and scope of the invention, which are not explicitly taught herein, but which are equivalent in function to those presented herein. For instance, it is possible to use a manual clamp to attain the similar results, albeit with a loss in automation of the entire procedure. Another preferred embodiment would utilize a servo motor directly moving the clamp, replacing clamping cam 45.

Electronic control means are depicted schematically in Fig. 6. It includes a printed circuit board 70 (Fig. 2) mounted below the key pad which contains the microcontroller and controls the operation of the blade changer. In a preferred embodiment, the electronic controls are on-board, but alternatively they may be contained in an instrument housing separate from the blade changer. A suitable microcontroller for driving the operations of the blade changer is selected from the PIC family of microcontrollers, manufactured by Microchip, Inc., Chandler, AZ. One of ordinary skill in the electronic arts is able to select and implement an individual PIC controller for these purposes. The "blade advance" signal comes to the microcontroller circuit from user-activated push-button switch located on keypad 75, also a part of the control means. In a preferred embodiment the power for the blade changer is supplied from the on-board battery 86. Alternatively, power could be supplied from an AC adapter. The electronic control means also enables the interlock function. The safety interlock feature hardware includes a touch memory device 150 (also known as a "data button") mounted on a blade cartridge, the microcontroller, touch memory reader, and electronically-controlled locking mechanisms for the cartridges 40. The interlock function is described in more detail below.

Disposable microtome blade cartridges are described herein with new and useful advantages. As shown in cross-section C-C (Fig. 3C), supply cartridge 15 comprises a body 105, having sides 110, 115, and a top portion 120 having a groove or slot 125 adapted for receiving rail portion 130 of dispensing tab 90. Sides 110 and 115 each have

a guide slot 117 machined into them for engaging cartridge guides 119. In a preferred embodiment the guides are rod-shaped and are mounted to the upper stage and are positioned so that when a cartridge engages the guides it is correctly positioned relative to the support plate 25 and the loading segment 30. Spring 107 is contained within body 105 and serves to urge the blade stack 135 upwardly towards the blade exit 140. Any conventional spring type may be used, including leaf springs, helical springs, and even a spring member integral to the body 105, such as a molded plastic tab. A touch memory device 150 is attached to the cartridge and contains the information pertaining to the contents of the cartridge, such as the number of blades, type, lot number, expiration, and related information. The touch memory device enables communication between the cartridge and the blade changer, thus adding an element of intelligence to the blade changer.

The supply cartridge may also serve to function as a waste cartridge for accepting spent blades. Again with reference to Fig. 3C, cross-section C-C shows an entrance 145 for used blades. The supply cartridge is oriented on upper stage body 5 in reverse so that entrance 145 receives spent blades as they are pushed out of the cutting position by a new blade. As the user continues to load new blades, used blades accumulate in the reversed supply cartridge now functioning as a waste cartridge. Spring 107 will be pushed towards the top 120 of the cartridge as waste blades accumulate. The microcontroller will signal the user that the waste cartridge is filled when the microcontroller has recorded the maximum number of allowable blades. Alternatively, a dedicated waste cartridge is also possible, and is depicted in Figs. 5A-C.

Again with reference to Fig. 3, supply cartridge 15 has a dispensing tab 90 integral with the cartridge and adapted for engaging each new blade 95. Downward protrusion 92 engages a slot or opening in each new blade. The downward protrusion may be a metal tab, a plastic hook or similar equivalent article. The main design limitation is that it reliably contact only one blade at a time. Downward protrusion 92 may be located anywhere on dispensing tab 90 so long as it functions to urge a single blade out of the cartridge for each cycle of the loading segment 30. In the preferred embodiment shown in Fig. 3, the protrusion is forward mounted on the blade side of dispensing tab 90. A second embodiment of the dispensing tab is shown in Figs. 7-8.

The primary feature is that dispensing tab shown (290) is designed with a slot or cutout for engaging shuttle tab 231. It does not have the teeth necessary for engaging the loading segment 30, which is not present in this embodiment.

The safety interlock feature will now be described with more particularity. The safety interlock feature includes touch memory device 150 mounted on the cartridge, an on-board PIC microcontroller contained within the blade changer for running the operations of the device while being in communication with the touch memory device, a contact reader for the data button, and electronically-controlled locking mechanisms for the cartridges. The touch memory device is described in U.S. Serial Number 08/995,052, filed December 19, 1997, incorporated herein by reference in its entirety. In a preferred embodiment, the memory device is an EPROM such as the Dallas Semiconductor DS1985 F5 16 Kbit add-only touch memory device. Its primary function is to initialize the safety interlock system for each new blade cartridge that is presented to the blade changer. The touch memory device contains information such as the number of blades, date of expiration, lot no., etc. In operation, the touch memory device is initially read-in the number of blades in the cartridge when loaded with blades at the factory. When the cartridge is loaded into the supply position on the blade changer, contacts on the cartridge connected to the touch memory device, or the touch memory device itself, make electrical contact with a touch memory reader (not shown) which is built into the upper stage so that as the cartridge seats itself it contacts the touch memory reader. The on-board microcontroller then tracks the position and number of blades left in the cartridge until the cartridge is empty. The on-board microcontroller will then notify the user through an interface such as LEDs or LCD readout. The on-board microcontroller executes the blade loading functions and maintains a look-up table that correlates blade position with steps executed, and so it tracks where the blades are at all times, and most importantly, whether blades are outside of the cartridges (and a potential safety hazard). If they are, then the interlock function will not allow the cartridges to be removed until the blades are within their respective cartridges. Safety interlocks 155 are mechanical- or solenoid-operated latches or arms that retain the cartridge in position, until activated by the microcontroller to release the cartridge. A hole or other ledge for the latch to attach to is located on the cartridge on the side facing the upper stage.

The cycle portion of the operation of the blade changer will now be described, with particular reference to Figs. 2 and 4. Starting with loading a new blade cartridge, a new supply cartridge 15 is loaded into the upper stage body 5, and locks into position. To eject a new blade 95 from supply cartridge 15, the user presses the blade advance push-button on key pad 15. Switch 15 is in electrical communication with the microcontroller which then activates motor 10. Motor 50 is actuated driving gear 55 and pulley 60 which cause rotation of drive shaft 65. This action then causes the loading and clamping cams 40 and 45, respectively, to move in fixed relation with each other. These cams are oriented on the drive shaft so that the clamping cam 45 is not engaged with the clamping plate 20 for the first half-turn of drive shaft 65 while loading cam 40 is moving loading segment 30 from right to left and consequently dispensing tab 90 moves the first part of the new blade into the cutting area.

During the second half-turn of drive shaft 65 clamping cam 45 engages with clamping plate 20 causing the blade to be clamped in the cutting position while the loading cam 40 moves the loading segment 30 and the dispensing tab 90 from left to right. In the middle of this move the microcontroller stops motor 50 and the blade 100 stays clamped ready for cutting.

When the new blade 95 is pushed from the supply cartridge 15 to the cutting area it pushes used blade 100 from the cutting area to waste cartridge 10. This design allows partial movement of the new blade 95 in one direction (1/3 of a blade width with each back-and-forth cycle of the loading segment), in order to maximize use of the blade for small tissue blocks. It takes three full cycles of the dispensing tab to fully eject and position new blade 95. More particularly and with reference to Figs. 4A-4D, Fig. 4A shows the supply cartridge 15 at rest with the new blade 95 concealed from view within the cartridge (start position). As loading segment 30 (not shown in this view) is activated, it engages the teeth on dispensing tab 90 which then pushes new blade 95 one third of its length out of the housing (Fig. 4B). As loading cam 40 rotates, the direction of dispensing tab 90 is then reversed by loading segment 30, and the tab moves back to its starting position. The second cycle repeats the left-right motion of the dispensing tab, pushing the blade yet another one-third of its length (Figs. 4C and 4D) per cycle. Fig. 4D shows a fully ejected new blade 95. Clearly an alternative embodiment which

pushes the blade out a different fraction of its length, such as  $\frac{1}{4}$ , or  $\frac{1}{5}$ , is also within the spirit and scope of this invention.

Referring again to Fig. 2, used blade 100 is pushed out of its cutting position by the action of the new blade 95 being urged out of the supply cartridge, as previously described. The two blades occupy the same plane, and so as a new blade is ejected, it engages the old blade at their common edges. Used blade 100 is pushed into waste cartridge 10, which may be an empty supply cartridge adapted to fit into upper stage body 5 (Fig. 5), or it may be an empty supply cartridge being reversible and having an entrance 145, as previously described. In an alternate embodiment, a dedicated waste cartridge may be used. In Figs. 5A-C, such a cartridge is shown. It shares many of the same components as the supply cartridge.

A second embodiment of the blade changer comprises lower and upper stage bodies 201, 205, respectively. With reference to Figs. 7-8, the microtome blade cartridges are removably located within the upper stage body 205. The lower stage body is adaptable to a wide variety of rotary microtomes, and serves as the common interface mounting for the upper stage. The disposable blade cartridges 210, 215 are adapted to lock into the upper stage body 205 so as to provide an element of safety. The cartridges are described more fully in the first embodiment and in Figs. 3-5. In this second embodiment they differ only in that the dispensing tab 90 (Figs. 1-2) is replaced by dispensing tab 290 (Fig. 7-8). The cartridges are releasable only when the individual blades are fully secured within the body of the cartridge. This "interlock" function can be attained in many ways, however a preferred embodiment includes an on-board microcontroller which monitors the state of operation of the blade changer. When the controller's logic functions determine that no blade edges are exposed, then the clamping plate and/or the cartridges may be released. The interlock function is more fully described below. The clamping means includes clamping plate 20, support plate 25, and clamp pivot rod 112 which together function to clamp the blade in the cutting position during use of the blade in the microtome. Reverser shuttle 230 has a shuttle tab portion 231 mounted to engage the slot 231 in dispensing tab 290. Dispensing tab 290 is integral with the supply cartridge 215. Reverser shuttle 230 has a threaded portion (not shown) which engages reverser screw 240. The function of reverser shuttle 230 is to

move dispensing tab 290 of the blade supply cartridge 215 thereby urging new blades 95 to the central cutting area. As shown by Figs 3-4, this is performed through downwardly protruding member 92 which engages a slot or hole 96 formed in the body of blade 95 which enables dispensing tab 290 to engage the topmost blade in its stored position at the top of the stack of blades contained within supply cartridge 215. Reverser screw 240 is supported on either end by bearings 241 which are supported and retained by upper stage body 205. Reverser shuttle 230 engages reverser screw 240 through the helical cutout 232 and mating helical threads (not shown) located on the shuttle 230. In a preferred embodiment, reverser shuttle 230 acts like a threaded nut and moves laterally at the urging of reverser screw 230. The helical cutout of reverser screw 230 is unique in that the reverser shuttle will move back and forth without a concomitant change in direction of any other component in the drive train. Similar reverser screws are common and well-known in the ink-jet printer art.

Power means comprises bidirectional DC motor 250 which rotates drive shaft 265 and drive gear 255, which in turn engages reverser screw gear 260. Reverser screw gear 260 in turn is attached to reverser screw 240, and when rotational motion is applied through drive shaft 265 the result is rotational motion in reverser screw 240, and thus the threads of reverser shuttle 230 will be urged to move laterally along the helical cutout. Drive shaft 265 also simultaneously moves clamping plate 20 forward and backward in order to either clamp or release a blade in the cutting area. The motor is bidirectional so that clamp pivot rod 112 may be released only when the motor is reversed. This function would require a clutch mechanism that in forward (normal) operation engages a groove in the rod, which stops the rod from being removed from the blade changer. Since removal of the rod is a precursor to removal of the clamping plate for cleaning access, this is another safety interlock feature of the device.

The reverser screw 240 and clamping cam 45 are coordinated so that reverser shuttle 230 can only push a new blade 95 into position when clamping plate 20 is open (pressure relieved from the blade). It is well within the skill in the art to design and position the two cams to effectuate this coordinated function.

The functional advantages of the invention described above are numerous. First, the blades are moved into the cutting area completely without manual contact. Second,

blades are moved into the waste cartridge for disposal completely without manual contact. Third, moving the blades automatically, by push-button switch or by manual lever, is a fast, efficient way to load and unload.

5 Although certain presently preferred embodiments of the invention have been described herein, it will be apparent to those skilled in the art to which the invention pertains that variations and modifications of the described embodiment may be made without departing from the spirit and scope of the invention. Accordingly, it is intended that the invention be limited only to the extent required by the appended claims and the applicable rules of law.